









PCB.WELDING DRAWING (TOLERANCE:±0.05)



Technical Index:

1. Temperature range: $-25^{\circ}\text{C}\sim+85^{\circ}\text{C}$.
2. Rated voltage: 600V, AC, DC.
3. Rated current: 5.0A AC, DC.
4. Contact resistance: $\leq 20\text{m}\Omega$.
5. Withstanding voltage: 1500V AC/minute.
6. Insulation resistance: $\geq 1000\text{M}\Omega$.

型号	CKT	A	B
MX3.0-2-1PWZ	2*1	0.00	6.00
MX3.0-2-2PWZ	2*2	3.00	9.00
MX3.0-2-3PWZ	2*3	6.00	12.00
MX3.0-2-4PWZ	2*4	9.00	15.00
MX3.0-2-5PWZ	2*5	12.00	18.00
MX3.0-2-6PWZ	2*6	15.00	21.00
MX3.0-2-7PWZ	2*7	18.00	24.00
MX3.0-2-8PWZ	2*8	21.00	27.00
MX3.0-2-9PWZ	2*9	24.00	30.00
MX3.0-2-10PWZ	2*10	27.00	33.00
MX3.0-2-11PWZ	2*11	30.00	36.00
MX3.0-2-12PWZ	2*12	33.00	39.00



序号	品名	材质	制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	ROSE			料号 PART NO.	MX3.0-2-NPWZ	版本 REV.	A
						.X±0.30	X.°±5°					品名 TITLE	MX3.0MM WAFER DIP TYPE	页次 SHEET	1/1
1	MX3.0双排弯针WTB胶芯	PA66 UL94V-0 黑色				.XX±0.25	X.X°±1°	审核 CHECK	LEO	客户料号 CUTM.NO.					
2	MX3.0双排弯针WTB端子	铜合金/表面镀锡				.XXX±0.15		核准 APPROVAL	JOHN	深圳市睿新晟业科技有限公司					
							单位 UNITS	MM	比例 SCALE						
1 2 3 4 5 6 7 8 9															