

修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
A0				2021-05-10

Specifications:

Contact resistance: $\leq 20\text{m}\Omega$
Insulation resistance: $\geq 500\text{M}\Omega$
Rated voltage: 100V AC DC
Rated current: 2.0A AC DC
Withstand Voltage: 500V AC/minute
Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
Housing: PA66 UL94V-0, Natural

包装数量：2K/包

PIN.	DIM A	DIM B	DIM C	DIM D
2pin	1.50	5.00	3.60	2.70
3pin	3.00	6.30	5.10	3.45
4pin	4.50	7.80	6.60	4.45
5pin	6.00	9.30	8.10	4.45
6pin	7.50	10.80	9.60	7.45
7pin	9.00	12.30	11.10	7.45
8pin	10.50	13.80	12.60	9.80
9pin	12.00	15.30	14.10	9.80
10pin	13.50	16.80	15.60	9.80
11pin	15.00	18.30	17.10	9.80
12pin	16.50	19.80	18.60	9.80
13pin	18.00	21.30	20.10	11.30
14pin	19.50	22.80	21.60	11.30
15pin	21.00	24.30	23.10	11.30
16pin	21.00	25.80	24.60	11.30

深圳市睿新晟业科技有限公司

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表				TITLE: 产品名称：ZE1.5胶壳			
X.X	± 0.30	X.X°	$\pm 3^{\circ}$	APPD: 核准：	PART NO: 产品编号：RXSY-ZE1.5-N*Y		
X.XX	± 0.30	X.XX°	$\pm 2^{\circ}$	CHECK: 校对：	DATE	SCALE	UNIT
X.XXX	± 0.10	X.XXX°	$\pm 1^{\circ}$	DRAW: 绘图：	2021-05-10	1:1	mm
							CODE NUMBER A018